



CARBÓN ACTIVADO

GRANULADO CASCARA DE COCO

COD - 93

Granular Activated Carbon (GAC) is manufactured from select grades of coconut shell and features a high density, large micropore volume and high surface area. It's commonly used for the purification of potable water, beverage manufacture, dialysis, aquarium water and a variety of food grade applications. In properly designed systems, will effectively remove chlorine, chloramines, lead, radon, MtBE, TCE, PCE, THM's, Phenols, pesticides, detergents, taste & odor, etc. meets AWWA Standard B-600-74, ANSI/NSF Standard 61 for drinking water applications.



TYPICAL PHYSICAL PROPERTIES / SPECIFICATIONS

Iodine Number, Min	1100
Apparent Density (ASTM 2854), g/cc	0.48 – 0.50
	lb/ft ³
	29-31
Abrasion No., min.	85
Particle Size – mesh size	12 x 40
	8 x30
CTC %, Min	55
Total Surface Area (BET), m ² /g	1100 - 1200
Ash (ASTM D-2866) -%w/w	3.0
Moisture, max as packed- % w/w	3%

STANDARD PACKAGING:

55lb or 27.5lb POLYLINE D POLYPROPYLENE BAGS. 200lb FIBER DRUMS. 1100lb SUPERSACKS.

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied for which we assume legal responsibility or that the information or goods is fit for any particular use either alone or in combination with other goods or processes.